

## 410 STRIPPER

concentrated amoniated stripper

#### HEAVY DUTY STRIPPER

Quickly penetrates through layers of old finish and wax and dissolves them for easy removal. Works on all kinds of floors; asphalt, rubber, vinyl asbestos, vinyl and clay tiles, linoleum, terrazzo and marble.

# EVAPORATION CONTROL

Stripper's controlled evaporation ingredients hold old finishes on surface longer to help prevent redepositing and drying.

## HARD WORKING FORMULA

Softens buildup of floor finish films, destroys the chemical bonding structure and emulsifies the fold finish for easy removal. This stripper keeps on working where other strippers leave off.

#### SUPER CONCENTRATED

Economy. Can be diluted with 5 pats of water for stripping heavy buildup and up to 1 to 40 for light stripping.



#### **DESCRIPTION**

This stripper is especially formulated to remove all types of floor waxes and finishes from all kinds of floors. It works in a new way to penetrate quickly the most stubborn wax and polymer finish films so they can be removed more readily.

#### **APPLICATION**

For use on all types of floors including:

Asphalt, Concrete, Marble, Quarry tile, Stone, Rubber, Terrazzo, Vinyl, Vinyl Asbestos, Ceramic tile

#### **DIRECTIONS FOR USE**

Mix STRIPPER with warm (not hot) water. Hard water will not hamper stripper. Use the following dilutions (expressed as 1 part STRIPPER to *x* parts of water): 1 to 2 - For floors that have been badly neglected. 1 to 5 - For non-buffable, metal cross-linked polymer finishes or for very heavy buildup of finishes (1 gal of mix for 250 sq ft of floor). 1 to 10 - For buffable waxes and water-resistant waxes. 1 to 20 -For non-water resistant waxes. 1 to 40 - for new, previously unfinished floors to remove oily coatings placed there by the manufacturer.

- Soak (do not flood) an area not over 10 x 20 ft., and let stand for 5-10 minutes.
- Seal old or porous floor with a floor sealer before refinishing floor.

### **SPECIFICATIONS**

Packaged:	Drums, 5- gallon Enviro-pak, 4- 1 gallons
Appearance:	Clear liquid
Odor:	Ammoniacal
pH:	13.00
Flash point:	None. Non-flammable
Solubility in water:	Complete

### **PRECAUTIONS**

Keep out of reach of children. Do not take internally. Keep out of eyes. Avoid prolonged skin contact. Do not mix with chlorine-type bleaches. Do not inhale vapor. Rinse empty container with water and discard. This product is intended for industrial and commercial use and storage by trained service persons only. Manufacturer will not be responsible for any injury, loss, or damage, if product is used in any manner not in compliance with label directions or if precautions are not observed.

### **FIRST AID**

EYES: Flush with large amounts of water for at least 15 minutes; contact physician. IF SWALLOWED: Induce vomiting. Drink large quantities of water. Seek medical attention. EXTERNAL: Flush with large amounts of water. Remove contaminated clothes. Seek medical attention.

5/97 1738